```
who lived sometime between the 6th and 4th century BC.<sup>[2][3]</sup> His notation to describe Sanskrit word structure is equivalent in power to that of Backus and has many similar properties.
In Western society, grammar was long regarded as a subject for teaching, rather than scientific study; descriptions were informal and targeted at practical usage. In the first half of the 20th century,
linguists such as Leonard Bloomfield and Zellig Harris started attempts to formalize the description of language, including phrase structure.
Meanwhile, string rewriting rules as formal logical systems were introduced and studied by mathematicians such as Axel Thue (in 1914), Emil Post (1920s-40s) and Alan Turing (1936). Noam
Chomsky, teaching linguistics to students of information theory at MIT, combined linguistics and mathematics by taking what is essentially Thue's formalism as the basis for the description of the
syntax of natural language. He also introduced a clear distinction between generative rules (those of context-free grammars) and transformation rules (1956). [4][5]
John Backus, a programming language designer at IBM, proposed a metalanguage of "metalinguistic formulas"[1][7][8] to describe the syntax of the new programming language IAL, known today as
ALGOL 58 (1959). His notation was first used in the ALGOL 60 report.
BNF is a notation for Chomsky's context-free grammars. Backus was familiar with Chomsky's work. [9]
As proposed by Backus, the formula defined "classes" whose names are enclosed in angle brackets. For example, <ab>. Each of these names denotes a class of basic symbols. [1]
Further development of ALGOL led to ALGOL 60. In the committee's 1963 report, Peter Naur called Backus's notation Backus normal form. Donald Knuth argued that BNF should rather be read as
Backus-Naur form, as it is "not a normal form in the conventional sense",[10] unlike, for instance, Chomsky normal form. The name Pāṇini Backus form was also once suggested in view of the fact
that the expansion Backus normal form may not be accurate, and that Pāṇini had independently developed a similar notation earlier.[11]
BNF is described by Peter Naur in the ALGOL 60 report as metalinguistic formula:[12]
      Sequences of characters enclosed in the brackets <> represent metalinguistic variables whose values are sequences of symbols. The marks "::=" and "I" (the latter with the meaning of
      "or") are metalinguistic connectives. Any mark in a formula, which is not a variable or a connective, denotes itself. Juxtaposition of marks or variables in a formula signifies juxtaposition
      of the sequence denoted.
Another example from the ALGOL 60 report illustrates a major difference between the BNF metalanguage and a Chomsky context-free grammar. Metalinguistic variables do not require a rule
defining their formation. Their formation may simply be described in natural language within the \Leftrightarrow brackets. The following ALGOL 60 report section 2.3 comments specification, exemplifies how
this works:
     For the purpose of including text among the symbols of a program the following "comment" conventions hold:
      The sequence of basic symbols:
                                                           is equivalent to
      ; comment <any sequence not containing ';'>;
      begin comment <any sequence not containing ';'>;
                                                           begin
      end <any sequence not containing 'end' or ';' or 'else'> end
     Equivalence here means that any of the three structures shown in the left column may be replaced, in any occurrence outside of strings, by the symbol shown in the same line in the right
     column without any effect on the action of the program.
Naur changed two of Backus's symbols to commonly available characters. The := symbol was originally a := . The | symbol was originally the word "or" (with a bar over
it). [7]:14 [clarification needed] Working for IBM, Backus would have had a non-disclosure agreement and could not have talked about his source if it came from an IBM proprietary project. [citation needed]
BNF is very similar to canonical-form boolean algebra equations that are, and were at the time, used in logic-circuit design. Backus was a mathematician and the designer of the FORTRAN
programming language. Studies of boolean algebra is commonly part of a mathematics curriculum. What we do know is that neither Backus nor Naur described the names enclosed in < > as
non-terminals. Chomsky's terminology was not originally used in describing BNF. Naur later described them as classes in ALGOL course materials. [1] In the ALGOL 60 report they were called
metalinguistic variables. Anything other than the metasymbols ::= , | , and class names enclosed in < > are symbols of the language being defined. The metasymbols ::= is to be
interpreted as "is defined as". The | is used to separate alternative definitions and is interpreted as "or". The metasymbols < > are delimiters enclosing a class name. BNF is described as a
metalanguage for talking about ALGOL by Peter Naur and Saul Rosen.[1]
In 1947 Saul Rosen became involved in the activities of the fledgling Association for Computing Machinery, first on the languages committee that became the IAL group and eventually led to
ALGOL. He was the first managing editor of the Communications of the ACM. [clarification needed] What we do know is that BNF was first used as a metalanguage to talk about the ALGOL language in
the ALGOL 60 report. That is how it is explained in ALGOL programming course material developed by Peter Naur in 1962.<sup>[1]</sup> Early ALGOL manuals by IBM, Honeywell, Burroughs and Digital
Equipment Corporation followed the ALGOL 60 report using it as a metalanguage. Saul Rosen in his book<sup>[13]</sup> describes BNF as a metalanguage for talking about ALGOL. An example of its use as
a metalanguage would be in defining an arithmetic expression:
         <expr> ::= <term>|<expr><addop><term>
The first symbol of an alternative may be the class being defined, the repetition, as explained by Naur, having the function of specifying that the alternative sequence can recursively begin with a
previous alternative and can be repeated any number of times. [1] For example, above <expr> is defined as a <term> followed by any number of <addop> <term>.
In some later metalanguages, such as Schorre's META II, the BNF recursive repeat construct is replaced by a sequence operator and target language symbols defined using quoted strings. The
< and > brackets were removed. Parentheses ( ) for mathematical grouping were added. The <expr> rule would appear in META II as
         EXPR = TERM $('+' TERM .OUT('ADD') | '-' TERM .OUT('SUB'));
These changes enabled META II and its derivative programming languages to define and extend their own metalanguage, at the cost of the ability to use a natural language description,
metalinguistic variable, language construct description. Many spin-off metalanguages were inspired by BNF. [citation needed] See META II, TREE-META, and Metacompiler.
A BNF class describes a language construct formation, with formation defined as a pattern or the action of forming the pattern. The class name expr is described in a natural language as a
 <term> followed by a sequence <addop> <term>. A class is an abstraction; we can talk about it independent of its formation. We can talk about term, independent of its definition, as being
added or subtracted in expr. We can talk about a term being a specific data type and how an expr is to be evaluated having specific combinations of data types, or even reordering an expression to
group data types and evaluation results of mixed types. The natural-language supplement provided specific details of the language class semantics to be used by a compiler implementation and a
programmer writing an ALGOL program. Natural-language description further supplemented the syntax as well. The integer rule is a good example of natural and metalanguage used to describe
syntax:
         <integer> ::= <digit>|<integer><digit>
There are no specifics on white space in the above. As far as the rule states, we could have space between the digits. In the natural language we complement the BNF metalanguage by explaining
that the digit sequence can have no white space between the digits. English is only one of the possible natural languages. Translations of the ALGOL reports were available in many natural
languages.
The origin of BNF is not as important as its impact on programming language development. [citation needed] During the period immediately following the publication of the ALGOL 60 report BNF was
the basis of many compiler-compiler systems.
Some, like "A Syntax Directed Compiler for ALGOL 60" developed by Edgar T. Irons and "A Compiler Building System" Developed by Brooker and Morris, directly used BNF. Others, like the
Schorre Metacompilers, made it into a programming language with only a few changes. <class name> became symbol identifiers, dropping the enclosing <,> and using quoted strings for
symbols of the target language. Arithmetic-like grouping provided a simplification that removed using classes where grouping was its only value. The META II arithmetic expression rule shows
grouping use. Output expressions placed in a META II rule are used to output code and labels in an assembly language. Rules in META II are equivalent to a class definitions in BNF. The Unix
utility yacc is based on BNF with code production similar to META II. yacc is most commonly used as a parser generator, and its roots are obviously BNF.
BNF today is one of the oldest computer-related languages still in use. [citation needed]
Further examples [edit]
BNF's syntax itself may be represented with a BNF like the following:
                         ::= <rule> | <rule> <syntax>
    <syntax>
                          ::= <opt-whitespace> "<" <rule-name> ">" <opt-whitespace> "::=" <opt-whitespace>
    <rule>
   <expression> <line-end>
   <opt-whitespace> ::= " " <opt-whitespace> | ""
                         ::= <list> | t> <opt-whitespace> "|" <opt-whitespace> <expression>
    <expression>
                         ::= <opt-whitespace> <EOL> | <line-end> <line-end>
    end>
                         ::= <term> | <term> <opt-whitespace> <list>
    st>
                        ::= teral> | "<" <rule-name> ">"
    <term>
   teral>
                         ::= '"' <text1> '"' | "'" <text2> "'"
                         ::= "" | <character1> <text1>
    <text1>
    <text2>
                         ::= '' | <character2> <text2>
                         ::= <letter> | <digit> | <symbol>
    <character>
   <letter> ::= "A" | "B" | "C" | "D" | "E" | "F" | "G" | "H" | "I" | "J" | "K" | "L" | "M" | "N" | "O"
   | "P" | "Q" | "R" | "S" | "T" | "U" | "V" | "W" | "X" | "Y" | "Z" | "a" | "b" | "c" | "d" | "e" | "f" | "g" |
  "h" | "i" | "j" | "k" | "l" | "m" | "n" | "o" | "p" | "q" | "r" | "s" | "t" | "u" | "v" | "w" | "x" | "y" |
```

The original BNF did not use quotes as shown in teral> rule. This assumes that no whitespace is necessary for proper interpretation of the rule. <E0L> represents the appropriate line-end specifier (in ASCII, carriage-return, line-feed or both depending on the operating system). <rul><rul><rul><rul>-nameand <text> are to be substituted with a declared rule's name/label or literal text, respectively. In the U.S. postal address example above, the entire block-quote is a syntax. Each line or unbroken grouping of lines is a rule; for example one rule begins with <name-part> ::= . The other part of that rule (aside from a line-end) is an expression, which consists of two lists separated by a pipe | | . These two lists consists of some terms (three terms and two terms, respectively). Each term in this particular rule is a rule-name. Variants [edit] EBNF [edit] Main article: Extended Backus-Naur form There are many variants and extensions of BNF, generally either for the sake of simplicity and succinctness, or to adapt it to a specific application. One common feature of many variants is the use of regular expression repetition operators such as \* and + . The extended Backus-Naur form (EBNF) is a common one. Another common extension is the use of square brackets around optional items. Although not present in the original ALGOL 60 report (instead introduced a few years later in IBM's PL/I definition), the notation is now universally recognised. ABNF [edit] Augmented Backus–Naur form (ABNF) and Routing Backus–Naur form (RBNF)<sup>[14]</sup> are extensions commonly used to describe Internet Engineering Task Force (IETF) protocols. Parsing expression grammars build on the BNF and regular expression notations to form an alternative class of formal grammar, which is essentially analytic rather than generative in character. Others [edit] Many BNF specifications found online today are intended to be human-readable and are non-formal. These often include many of the following syntax rules and extensions: Optional items enclosed in square brackets: [<item-x>]. • Items existing 0 or more times are enclosed in curly brackets or suffixed with an asterisk (\*) such as <word> ::= <letter> {<letter>} or <word> ::= <letter> <letter>\* respectively. • Items existing 1 or more times are suffixed with an addition (plus) symbol, +, such as <word> ::= <letter>+. • Terminals may appear in bold rather than italics, and non-terminals in plain text rather than angle brackets. • Where items are grouped, they are enclosed in simple parentheses. BNF syntax diagram Software using BNF [edit] ANTLR, another parser generator written in Java Qlik Sense, a BI tool, uses a variant of BNF for scripting [15]

```
• BNF Converter (BNFC<sup>[16]</sup>), operating on a variant called "labeled Backus-Naur form" (LBNF). In this variant, each production for a given non-terminal is given a label, which can be used as a
 constructor of an algebraic data type representing that nonterminal. The converter is capable of producing types and parsers for abstract syntax in several languages, including Haskell and
 Java.

    Coco/R, compiler generator accepting an attributed grammar in EBNF

• DMS Software Reengineering Toolkit, program analysis and transformation system for arbitrary languages

    GOLD BNF parser

    GNU bison, GNU version of yacc

• RPA BNF parser.[17] Online (PHP) demo parsing: JavaScript, XML
```

::= "0" | "1" | "2" | "3" | "4" | "5" | "6" | "7" | "8" | "9"

| ":" | ";" | ">" | "=" | "<" | "?" | "@" | "[" | "\" | "]" | "^" | "^" | "\" | "\" | "\" | "\"

::= <character> | "'"

::= <character> | '"'

::= <letter> | <digit> | "-"

::= <letter> | <rule-name> <rule-char>

<symbol> ::= "|" | "!" | "#" | "\$" | "&" | "(" | ")" | "\*" | "+" | "," | "-" | "." | "/"

```
• XACT X4MR System,<sup>[18]</sup> a rule-based expert system for programming language translation
• XPL Analyzer, a tool which accepts simplified BNF for a language and produces a parser for that language in XPL; it may be integrated into the supplied SKELETON program, with which the
  language may be debugged<sup>[19]</sup> (a SHARE contributed program, which was preceded by A Compiler Generator<sup>[20]</sup>)
• Yacc, parser generator (most commonly used with the Lex preprocessor)
• bnfparser<sup>2</sup>,<sup>[21]</sup> a universal syntax verification utility
• bnf2xml, [22] Markup input with XML tags using advanced BNF matching.
• JavaCC, [23] Java Compiler Compiler tm (JavaCC tm) - The Java Parser Generator.
```

```
    Wirth syntax notation – an alternative to BNF from 1977

    Definite clause grammar – a more expressive alternative to BNF used in Prolog

    Van Wijngaarden grammar – used in preference to BNF to define Algol68

    Meta-II – an early compiler writing tool and notation

References [edit]
```

```
are sequences of basic symbols. Class designations of this
                                                                        26 March 2015.
   kind are found in any description of a language. For
                                                                     7. A a b Backus, J. W. (1959). "The syntax and semantics of the
   describing ordinary natural languages designation like word,
                                                                        proposed international algebraic language of the Zurich ACM-
   verb, noun, are used. .[6]:5,Note 1
                                                                        GAMM Conference" . Proceedings of the International
2. ^ "Panini biography" ∠. School of Mathematics and Statistics,
                                                                        Conference on Information Processing. UNESCO. pp. 125-
   University of St Andrews, Scotland. Retrieved 2014-03-22.
                                                                        132.
3. A Ingerman, Peter Zilahy (March 1967). " "Pāṇini-Backus
                                                                     8. * Farrell, James A. (August 1995). "Compiler Basics:
   Form" Suggested". Communications of the ACM. Association
                                                                         Extended Backus Naur Form" ☑. Archived ☑ from the original
```

Racket's parser tools ☑, lex and yacc-style Parsing (Beautiful Racket edition)

Belr ☑, A parser generator written in C++11. It uses ABNF.

1. ^ a b c d e f g h The meaning of syntactic formula may be

further explained by saying that words enclosed in the

for Computing Machinery. 10 (3): 137.

earliest independent inventor.

Language grammars [edit]

brackets < > , like <ab> , denote classes whose members

doi:10.1145/363162.363165 2. S2CID 52817672 2. Ingerman

suggests that the Backus Normal Form be renamed to the

Pāṇini-Backus Form, to give due credit to Pāṇini as the

4. ^ Chomsky, Noam (1956). "Three models for the description

of language" [in] (PDF). IRE Transactions on Information

*Theory.* **2** (3): 113–24. doi:10.1109/TIT.1956.1056813 ∠.

5. ^ Chomsky, Noam (1957). *Syntactic Structures*. The Hague:

Archived from the original (PDF) on 2010-09-19.

Compiler Description Language (CDL)

Translational Backus–Naur form (TBNF)

Syntax diagram – railroad diagram

See also [edit]

''z''

<digit>

<character1>

<character2> <rule-name>

<rule-char>

Note that "" is the empty string.

```
Mouton.
                                                                    Retrieved April 18, 2015.
External links [edit]
 • Garshol, Lars Marius, BNF and EBNF: What are they and how do they work?™, NO: Priv.

    RFC 5234 ☑ — Augmented BNF for Syntax Specifications: ABNF.
```

RFC 5511 ☑ — Routing BNF: A Syntax Used in Various Protocol Specifications.

UK: CAM (the latter is missing the cover page, but is otherwise much cleaner)

```
    Bernhard, Algol-60 BNF™, DE: LRZ München, the original BNF.

    "BNF grammars for SQL-92, SQL-99 and SQL-2003", Savage ☑, AU: Net, freely available BNF grammars for SQL.

• "BNF Web Club", DB research , CH: Unige, archived from the original on 2007-01-24, retrieved 2007-01-25, freely available BNF grammars for SQL, Ada, Java.
• "Free Programming Language Grammars for Compiler Construction", Source code . The free country, freely available BNF/EBNF grammars for C/C++, Pascal, COBOL, Ada 95, PL/I.
```

13. ^ Saul Rosen (Jan 1967). Programming Systems and

York/NY: McGraw Hill. ISBN 978-0070537088.

16. ^ "BNFC", Language technology ∠, SE: Chalmers

adapted from XPL's "emitters" for System/360.

21. ^ "BNF parser<sup>2</sup>", *Source forge* ☑ (project)

15. ^ "Script Syntax - Qlik Sense on Windows" ☑. *Qlik.com*.

QlikTech International AB. Retrieved 10 January 2022.

18. ^ "Tools", *Act world* ∠, archived from the original ∠ on 2013-

19. A If the target processor is System/360, or related, even up to

z/System, and the target language is similar to PL/I (or,

indeed, XPL), then the required code "emitters" may be

20. ^ McKeeman, W. M.; Horning, J.J.; Wortman, D. B. (1970).

23. ^ "JavaCC" ☑. Archived from the original ☑ on 2013-06-08.

Compiler Generator . Prentice-Hall. ISBN 978-0-13-155077-

[hide]

Powered by MediaWiki

WIKIMEDIA

14. ^ RBNF ℃.

01-29

3.

22. ^ bnf2xml ∠

Retrieved 2013-09-25.

17. ^ "Online demo", RPatk™

Languages . McGraw Hill Computer Science Series. New

```
Metasyntax notations
 V •T •E
                                         ABNF · Backus-Naur form · Definite clause grammar · EBNF · Syntax Definition Formalism · TBNF · OMeta · Wirth syntax notation
Categories: Formal languages | Compiler construction | Metalanguages
```

• "BNF files related to the STEP standard", *Exp engine* (SVN), Source forge, archived from the original on 2012-12-25. Includes parts 11, 14, and 21 of the ISO 10303 (STEP) standard.

6. Naur, Peter (1961). "A COURSE OF ALGO L 60

on 5 June 2011. Retrieved May 11, 2011.

Communications of the ACM. 10 (3): 137.

9. A Fulton, III, Scott M. (20 March 2007). "John W. Backus

doi:10.1145/355588.365140 2. S2CID 47537431 2.

doi:10.1145/363162.363165 2. S2CID 52817672 2.

12. ^ Revised ALGOL 60 report section. 1.1."ALGOL 60" ℃.

• ISO/IEC 14977:1996(E) Information technology – Syntactic metalanguage – Extended BNF, available from "Publicly available", Standards , ISO or from Kuhn, Marcus, Iso 14977 (PDF),

(1924 - 2007)" 2. BetaNews. Inc. Retrieved Jun 3, 2014.

10. ^ Knuth, Donald E. (1964). "Backus Normal Form vs. Backus

11. A Ingerman, P. Z. (1967). " "Pāņini Backus Form" suggested".

Naur Form". *Communications of the ACM*. **7** (12): 735–736.

PROGRAMMING with special reference to the DASK ALGOL

system" (PDF). Copenhagen: Regnecentralen. Retrieved

This page was last edited on 15 June 2022, at 13:31 (UTC). Text is available under the Creative Commons Attribution-ShareAlike License 3.0; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization. Privacy policy About Wikipedia Disclaimers Contact Wikipedia Mobile view Developers Statistics Cookie statement